RADHASOAMI DAYAL KI DAYA RADHASOAMI SAHAI

WATER QUALITY MONITORING REPORT Most Probable Number (MPN) of Bacteria in Dayalbagh Wells

Permissible limit for MPN is <10 and for pH is 6.5 to 8.5

Date of Reporting : <u>28-Mar-2022</u> Date of Sampling : <u>26-Mar-2022</u>

MPN Of Bacteria in **Is MPN Below** KMnO₄ Colour pН Sample (Per ml) S.No. Name of Well Permissible Current Previous Current Previous Limit of 10? Current Previous Value Value Value Value 1 3.6 3.0 Yes Light Pink Light Pink 7.3 7.3 Gangavas " " 2 Daval Nagar 7.27.27.4 6.1 " " " 3 Prem Nagar 3.0 3.0 7.47.1" " " 4 Dunn Tubewell 3.6 7.4 7.4 6.1 5 " " " 7.3 Punjabi Farm 3.6 6.1 7.3 " " " 6 Dairy West 3.0 3.6 7.47.4" " " $\mathbf{7}$ Pavan Kuan 3.6 3.0 7.3 7.2" " " 8 **DEI** Dairv 3.5 3.6 7.57.59 3.6 3.0 " " " 7.47.4Ganga Jal " " " 10 7.2Gaushala 7.07.37.4

Remarks of Water Quality Research Group: TFA-Water Supply Dept., to be requested for treatment of well/s having Coliform Bacteria MPN >7.0 with Potassium Permanganate.

Remarks of Revered Chairman-ACE: Due to negligence on the part of maintenance staff the system remained inoperative despite apparent completion of system maintenance work as planned.



1) The study aims at continuous monitoring of potable well water to detect the presence of coliforms using the "multiple fermentation tube" or "most probable number" technique.

2) In this method measured portions of a water sample are placed in test-tubes containing a culture medium. The tubes are then incubated for a standard time at a standard temperature. It is customary to report the results of the multiple fermentation tube test for coliforms as a most probable number (MPN) index. This is an index of the number of coliform bacteria that, more probably than any other number, would give the results shown by the test.

3) As a standard remedy, Potassium Permanganate is added in the ratio of 0.1 gm per litre to well water if MPN exceeds permissible limit. If the pH is less than permissible limits i.e., it is acidic, Hydrated Lime Powder i.e., Ca(OH)₂ is added in the ratio of 0.037 gms per litre of water. The two remedial processes mentioned above are periodically repeated till the desired water quality is achieved.